

# SPEAKA

*Speaker & Kabel*

MODEL	TT 120/140
NORMAL/PEAK W	120/140
FREQUENCY HZ	38-2000
FREE AIR RESOUANCE FREQUENCY (HZ)	47.80
SPLO (SPL AT 1W)DB	87
IMPEDANCE OHM	8
VAS (ACOUS VOL)	38
QTS (TOTAL Q)	0.58
QMS (MECH Q)	4.2
QES (ELEC Q)	0.67
MOUNTING SIZE MM	184
WEIGHT KG	1250

# SPEAKA

*Speaker & Kabel*

MODEL	MT 75/90
NORMAL/PEAK W	75/90
FREQUENCY HZ	200-4000
FREE AIR RESOUANCE FREQUENCY (HZ)	110
SPLO (SPL AT 1W)DB	85
IMPEDANCE OHM	8
VAS (ACOUS VOL)	1.6
QTS (TOTAL Q)	0.84
QMS (MECH Q)	3.51
QES (ELEC Q)	1.1
MOUNTING SIZE MM	101
WEIGHT KG	390

MODEL	TT 180/200	MT 75/90	HT60/80
BEST NO.	300269	300237	300287
NORMAL/PEAK W	180/200	75/90	60/80
FREQUENCY Hz	28-1200	200-4000	3500-22000
SPL <sub>o</sub> (SPL AT 1W) db	88, 5	85	
IMPEDANCE OHM	8	8	8
VAS (Acous Vol)	141	1, 6	
Q <sub>ts</sub> (Total Q)	0, 54	0, 84	
Q <sub>ms</sub> (Mech Q)	3, 9	3, 51	
Q <sub>es</sub> (Elec Q)	0, 62	1, 1	
MOUNTING SIZE mm	282	101	
WEIGHT Kg	2350	390	120