

## Conductor markers TM-I 18 MC NE GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

### General ordering data

Type	TM-I 18 MC NE GE
Order No.	<a href="#">1718431687</a>
Version	Conductor markers, MultiCard, 18 x 4 mm, Polyamide 66, Colour: Yellow
GTIN (EAN)	4008190349028
Qty.	320 pc(s).

## Conductor markers TM-I 18 MC NE GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Length	18 mm	Width	4 mm
Height	1.7 mm	Depth	2 mm
Net weight	0.353 g		

### General data

Colour	Yellow	Material	Polyamide 66
Material colour according to resistance code	4	Number per sheet	64
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Recommended industries	Transportation, Machinery	Type of printing	blank
UL 94 flammability rating	V-2		

### Conductor and cable markers

Conductor O.D., max.	40 mm	Conductor O.D., min.	1 mm
Conductor cross-section, max.	500 mm <sup>2</sup>	Conductor cross-section, min.	0.22 mm <sup>2</sup>
Halogen	No		

### Classifications

ETIM 3.0	EC001530	UNSPSC	44-12-17-08
eClass 5.1	27-14-91-03	eClass 6.2	27-14-91-03
eClass 7.1	27-14-91-03		

### Approvals

Approvals	
ROHS	Conform

### Downloads

M-Print® PRO configuration file	<a href="#">mc_tm-i_18_mcf.zip</a>
---------------------------------	------------------------------------