

PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



PCB terminal block, Nominal current: 13.5 A, Nom. voltage: 240 V, Pitch: 3.5 mm, Number of positions: 4, Connection method: Spring-cage conn., Mounting: Soldering, Conductor/PCB connection direction: 45 °, Color: green

The figure shows a 10-position version of the product

Product Features

- 3.5 mm pitch
- Large terminal block capacity with compact dimensions
- Attractive design for connection at a glance
- Optional color coding
- Plug with optional mechanical coding
- Spring-cage double connection with direct plug-in technology with a release button

Key commercial data

| | |
|-------------------------|---------------|
| package_quantity | 50 |
| GTIN | 4046356128971 |

Technical data

Dimensions

| | |
|-----------------------|-----------|
| Pitch | 3.5 mm |
| Dimension a | 10.5 mm |
| Pin dimensions | 1,0 x 0,4 |
| Pin spacing | 3.5 mm |
| Hole diameter | 1.3 mm |

General

| | |
|---|-----------|
| Range of articles | PTDA 1,5/ |
| Insulating material group | I |
| Rated surge voltage (III/3) | 2.5 kV |
| Rated surge voltage (III/2) | 2.5 kV |
| Rated surge voltage (II/2) | 2.5 kV |
| Rated voltage (III/3) | 200 V |
| Rated voltage (III/2) | 240 V |
| Rated voltage (II/2) | 400 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 13.5 A |

PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

Technical data

General

| | |
|---|---------------------|
| Nominal cross section | 1.5 mm ² |
| Maximum load current | 13.5 A |
| Insulating material | PA |
| Solder pin surface | Sn |
| Inflammability class according to UL 94 | V0 |
| Stripping length | 10 mm |
| Number of positions | 4 |

Connection data

| | |
|---|---------------------|
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 1.5 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 1.5 mm ² |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.5 mm ² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1.5 mm ² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.5 mm ² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 0.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 16 |
| 2 conductors with same cross section, solid min. | 0.2 mm ² |
| 2 conductors with same cross section, solid max. | 1.5 mm ² |
| 2 conductors with same cross section, stranded min. | 0.2 mm ² |
| 2 conductors with same cross section, stranded max. | 1.5 mm ² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.5 mm ² |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 1.5 mm ² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm ² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm ² |
| Minimum AWG according to UL/CUL | 24 |
| Maximum AWG according to UL/CUL | 16 |

classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 272607xx |
| eCl@ss 4.1 | 27141109 |
| eCl@ss 5.0 | 27141190 |
| eCl@ss 5.1 | 27141190 |

PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27261101 |
| eCl@ss 7.0 | 27440401 |
| eCl@ss 8.0 | 27440401 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC002643 |
| ETIM 5.0 | EC002643 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211801 |
| UNSPSC 7.0901 | 39121432 |
| UNSPSC 11 | 34131203 |
| UNSPSC 12.01 | 39121432 |
| UNSPSC 13.2 | 39121432 |

approvals

UL Recognized / VDE Gutachten mit Fertigungsüberwachung / cUL Recognized / CCA / IECCE CB Scheme / GOST / GOST / cULus Recognized /

Approval details

| UL Recognized | | | |
|----------------------------|-------|-------|-------|
| Usegroups | B | C | D |
| Nominal voltage UN | 300 V | 150 V | 300 V |
| Nominal current IN | 12 A | 12 A | 10 A |
| mm ² /AWG/kcmil | 24-16 | 24-16 | 24-16 |

| | |
|--|---------|
| VDE Gutachten mit Fertigungsüberwachung | |
| Nominal voltage UN | 130 V |
| Nominal current IN | 17.5 A |
| mm ² /AWG/kcmil | 0.2-1.5 |


| | |
|-----------------------|--|
| cUL Recognized | |
|-----------------------|--|


PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

approvals


| Usegroups | B | C | D |
|----------------------------|-------|-------|-------|
| Nominal voltage UN | 300 V | 150 V | 300 V |
| Nominal current IN | 12 A | 12 A | 10 A |
| mm ² /AWG/kcmil | 24-16 | 24-16 | 24-16 |

| CCA | |
|----------------------------|---------|
| Nominal voltage UN | 130 V |
| Nominal current IN | 17.5 A |
| mm ² /AWG/kcmil | 0.2-1.5 |

| IECEE CB Scheme  | |
|---|---------|
| Nominal voltage UN | 130 V |
| Nominal current IN | 17.5 A |
| mm ² /AWG/kcmil | 0.2-1.5 |

| GOST  | |
|--|--|
|--|--|


|  | |
|---|--|
|---|--|

| cULus Recognized  | |
|--|--|
|--|--|

Drawings


PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

Drilling diagram



PCB terminal block - PTDA 1,5/ 4-3,5 - 1724938

Diagram



Derating diagram for 5 positions; reduction factor=0.8

Dimensioned drawing

